

528,061
10/52061

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number
WO 2004/030551 A1

(51) International Patent Classification: **A61B 18/00**

International Application Number:

PCT/SE2003/001537 ✓

International Filing Date: 2 October 2003 (02.10.2003)

Original Language: Swedish

Publication Language: English

Priority Data: **04 Apr 05**
0258-5 4 October 2002 (04.10.2002) SE

(72) Applicant (for all designated States except US): **PLASMA SURGICAL INVESTMENTS LIMITED** [GB/GB]; Sea Meadow House, P.O. Box 116, Road Town, Tortola (VG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SUSLOV, Nikolay** [RU/SE]; Hängestensvägen 45, S-421 67 Västra Frölunda (SE).

(74) Agent: **AWAPATENT AB**; Box 11394, S-402 28 Göteborg (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to the identity of the inventor (Rule 4.17(i)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR,

[Continued on next page]

(54) Title: **PLASMA SURGICAL DEVICE**



(57) Abstract: A plasma surgical device for reducing bleeding in live tissue by means of a gas plasma. The device comprises a plasma-generating system having an anode (1), a cathode (8) and a gas supply channel (17) for supplying gas to the plasma-generating system, the plasma-generating system comprising at least one electrode (3, 5), which is arranged between said cathode (8) and said anode (1), and the plasma-generating system being enclosed by a housing (12) of an electrically conductive material, which is connected to the anode (1). The device is characterised in that said housing (12) forms said gas supply channel (17).

BEST AVAILABLE COPY

WO 2004/030551 A1



HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

PLASMA SURGICAL DEVICEField of the Invention

The present invention relates to a plasma surgical device for reducing bleeding in live tissue by means of a gas plasma, comprising a plasma-generating system having an anode, a cathode and a gas supply channel for supplying gas to the plasma-generating system, the plasma-generating system further comprising at least one electrode, which is arranged between said cathode and said anode, and the plasma-generating system being enclosed by a housing of an electrically conductive material, which is connected to the anode.

Background Art

Plasma surgical devices here means devices of the kind used in surgery to stop bleeding by means of a gas plasma. Such gas-plasma-producing devices have the shape of a pen that can be easily applied to a desired area, for example bleeding tissue. At the tip of the pen, a gas plasma is present, the very high temperature of which causes coagulation and a haemostatic effect by a necrosed layer being formed like a crust over the tissue adjacent to the tip.

WO 96/06572 (Suslov) discloses a plasma surgical device according to prior art. This device has an electrically conductive body, which is connected to a positive pole of an energy source having a positive potential. Moreover, the body is formed with a cylindrical channel designed to heat the plasma-generating gas, which channel is formed from a number of sections that are electrically insulated from each other. The device has a cathode consisting of an electrically conductive tube, on one end of which an electrode is mounted. The other end

of the tube is connected to a negative pole of an energy source. This end of the tube is also connected to a gas supply unit to allow gas to be supplied to the device through the cathode tube.

5 In use, gas is supplied to the device through the cathode tube, while at the same time a voltage is applied across the positive and the negative pole, so that a voltage difference is obtained between the cathode and the electrically conductive body. Initially, the voltage
10 difference generates an electric arc, which heats the gas supplied to form a plasma, which is then maintained.

US-A-3,991,764 (Incropera, et al) discloses another device according to prior art. Here as well gas is supplied through a tube that is electrically connected to
15 the cathode of the device and runs into said cathode. Here the anode of the device is realised by a conductive body, which in turn is enclosed by a housing. Furthermore, water lines are provided for cooling the device.

A further device of this type is disclosed in WO
20 92/19166 (Nauchno-Issledovatel'sky Institut).

Owing to the recent developments in surgical technology open surgery is being used less and less, whereas laparoscopic (key-hole) surgery is being used more often. This implies new demands on the instruments used, in particular it must be possible to manufacture relatively
25 small instruments. Similarly, increased efficiency requirements in medical care have led to the abandonment of instruments that require special processes, for example sterilisation, after each use.

30 The object of the present invention is therefore to provide a plasma surgical device which satisfies one or more of the requirements stated above.

Summary of the Invention

35 The above object is achieved by means of a device as described by way of introduction, in which the housing forms said gas supply channel.

This construction allows less bulky instruments to be designed, which facilitates their use in laparoscopic surgery. Furthermore, it allows cost-efficient manufacturing of the instruments, thereby making it possible to
5 make them available as ready-sterilized, disposable instruments.

Suitably, the housing forms, in addition to said gas supply channel, an additional channel. This channel can be used for different purposes, conveniently to allow a
10 fluid to flow through it. For example, the additional channel can be used for supplying or discharging a coolant or for removing liquids from an area where surgery is performed, etc.

Preferably, the housing forms, in addition to said
15 gas supply channel, at least two additional channels. This design is particularly simple and space-saving. Advantageously, the gas supply channel can be centrally mounted in the housing, and the additional channels arranged along the circumference of the gas supply channel.
20 In this case, the additional channels are preferably cooling channels for respectively supplying and discharging a coolant.

Thus, one way of describing it is that the housing forms a supply portion, in which said gas supply channel
25 is formed, and a plasma-generating portion, in which said plasma-generating system is provided. This means that the cross section of the housing in the gas supply portion can be such as to form one or more channels, whereas the cross section in the plasma-generating portion is such as
30 to allow for the plasma-generating system. The length of the different portions can be varied depending on the application for which the device is intended.

The plasma-generating system comprises, in per se known manner, a cathode which is connected to a conductor
35 for connection to a source of electric energy. Preferably, said conductor extends through any one of the channels in said tubular housing, suitably through a cen-

trally arranged gas supply channel. The gas will then flow about the conductor towards the plasma-generating system and the cathode.

5 The plasma-generating system further comprises at least one electrode, which is mounted between said cathode and anode. Preferably, the plasma-generating system comprises at least two electrodes, which are insulated from each other by an insulating means. By using two electrodes that are insulated from each other the
10 risk of undesirable, double electric arcs being generated in the system is reduced. The electrode or electrodes, and any insulators, are suitably of annular cross section and form a channel in which the plasma is heated between the cathode and the anode.

15 The electrodes, and any insulators, are conveniently mounted in a holding means of an electrically insulating material. To ensure easy manufacture and a reliable construction, the electrodes, and any insulators, can advantageously be press fitted to said holding means.

20 Moreover, the cathode holder can suitably be mounted in such manner in the holding means that the cathode is positioned concentrically with and spaced from an electrode closest to the cathode, advantageously by the cathode being mounted in the holding means with the aid
25 of a cathode holder that is press fitted to the holding means.

In this way, the holding means forms a convenient assembly unit for keeping the electrodes and insulators together and for ensuring that the cathode is kept in the
30 correct position relative thereto. To prevent the holding means from being damaged because of the very high temperatures occurring around the cathode (up to 3200°C), an insulating tube of a ceramic material is conveniently mounted on the inside of the holding means so as to en-
35 close the cathode, for the protection of the holding means.

Furthermore, the holding means suitably has a connection end, which is connected to said gas supply channel, so that gas is passed through the holding means to the cathode and then on through said at least one electrode towards the anode. However, the holding means preferably has an outer shape that allows a fluid to flow respectively from and to the additional channels, so that the fluid can reach a space formed between the holding means, including said electrode and any insulators, and the inner wall of the tubular housing. Thus, the outer shape of the holding means should not block the outlets and inlets, respectively, of the additional channels in the plasma-generating portion.

Suitably, a gasket can be provided between the anode
15 and an electrode closest to the anode. In this case, the plasma-generating system is arranged in such manner in the housing that the anode is connected to the housing, a predetermined compressive force being applied to the gasket. In this way, a watertight seal is ensured between
20 the housing and the anode and electrical contact is established between the two.

Moreover, the housing can be surrounded by a first contact ring that is in electrical contact therewith, which contact ring is connected to earth. This makes the
25 instruments safer for the user. In this case, a second contact ring, which is electrically connected to the housing, may also be provided, which ring is capable of being used to constantly control the earthing of the housing.

Suitably, a connecting device is provided for con-
30 necting the gas supply to said gas supply channel and any desired function to the additional channels, such as the supply of coolant or suction power for evacuating liquid. The connecting device can have an outlet end, which
35 defines connecting channels for obtaining a fluidtight fit in said gas supply channel and additional channels, and an inlet end provided with hose couplings for con-

necting hoses to each of said connecting channels.
Furthermore, the connecting device can also have a conductor opening through which the cathode conductor can extend for connection to a voltage source. In this way,
5 the device can be easily connected to one or more supply units, adapted to supply, for example, energy, gas and coolant supply, etc.

Moreover, the device can suitably comprise a handle portion, which at least partially encloses said housing
10 for easy handling of the device.

To allow different kinds of devices to be connected to one and the same supply unit, adapted to supply, for example, gas, coolant or energy, the device can advantageously comprise a circuit adapted to distinguish the
15 type of device. This circuit comprises a component whose electric resistance is selected to represent the device type. Advantageously, the electric resistance can be read with reference to one of the earthed contact rings. By reading the electric resistance an indication of what
20 kind of device is connected to the supply unit is obtained. Examples of different kinds of devices are instruments intended for open surgery and instruments intended for laparoscopic surgery.

Further features and advantages of the present invention will be apparent from the following description of one particular embodiment of the invention, reference being made to the accompanying drawings.

Brief Description of the Drawings

30 Fig. 1 is an exploded view of one embodiment of the device according to the invention.

Fig. 2 is a view seen from the plasma-generating portion of the housing of the device shown in Fig. 1.

Fig. 3 is an exploded view of the cathode conductor and the plasma-generating system of the device shown in
35 Fig. 1.

Fig. 4 illustrates the holding element, with electrodes, of the device shown in Fig. 1.

Fig. 5 illustrates the device in Fig. 1 when assembled, the plasma-generating system being exposed.

5 Fig. 6 illustrates the device in Fig. 1 when assembled.

Fig. 7 illustrates a coupling terminal adapted to effect a connection to a supply unit adapted to supply gas, coolant and energy.

10 Fig. 8 illustrates the mounting of the device in Fig. 1 in a handle portion.

Fig. 9 illustrates the device with the handle portion according to Fig. 8.

Fig. 10 illustrates a second embodiment of a device
15 according to the invention.

Description of a Preferred Embodiment of the Invention

Fig. 1 is an exploded view of one embodiment of a plasma surgical device according to the invention. The device comprises an elongate housing 12, which encloses a
20 plasma-generating system for generating a plasma that is discharged at the end of the housing 12 and used to stop bleeding.

Fig. 1 illustrates the housing 12 as removed from
25 the plasma-generating system. As shown in Fig. 1 the housing has a supply portion (furthest away in the figure) and a plasma-generating portion (in the foreground of the figure), in which the plasma-generating system is mounted. The supply portion forms a gas supply
30 channel 17 and, in this case, two additional channels 15, 16, which are used as cooling channels. The housing 12 is here formed from a tubular section.

Fig. 2 illustrates the housing 12 as seen from the end of the plasma-generating portion (in the foreground
35 of the figure). This view shows the cross section of the supply portion of the housing 12. The gas supply channel 17 is arranged at the centre of the tubular housing 12

and the cooling channels 15, 16 are arranged along the circumference of the gas supply channel 17. Here the gas supply channel 17 is circular in cross section, whereas the cooling channels 15, 16 are C-shaped in cross section and together extend along the greater part of the circumference of the gas supply channel 17.

In the plasma-generating portion, the housing 12 is single circular in cross section and formed by an extension of the outer walls of the cooling channels 15, 16.

10 The housing 12 is formed of an electrically conductive material, suitably one that is appropriate for manufacturing units with the above-described cross sections, such as aluminium.

Fig. 1 also shows the plasma-generating system lying beside the housing 12. The system comprises an anode 1, a cathode 8 (see Fig. 3) and a set of electrodes 3, 5 disposed therebetween. The electrodes 3, 5 are annular and form, in per se known manner, a channel in which the plasma is heated before it is discharged at the anode 1.

20 Fig. 3 shows more clearly the plasma-generating system. The system comprises a cathode 8, which is mounted in a cathode holder 9, which in turn is connected to an electrical conductor 11 for connection to a source of electric energy. The conductor 11 is enclosed by an insulator 10.

The cathode holder 9 is designed to be fitted in a certain position in a holder element 7, which is formed of an insulating material, such as a temperature resistant plastic material. To protect the holder element 7 from the high temperatures (up to 3200°C) that may occur around the cathode, a cylindrical insulating tube 6 is provided in the holder element 7, between the cathode 8 and the inside of the holder element 7. Suitably, the insulating tube 6 is made of a heat-insulating ceramic material.

35 Furthermore, electrodes 5, 3, separated by insulators 4, are arranged in the holding means in such manner

that they form a channel for heating the plasma. Here, two electrodes 5, 3 are provided, which are separated by one insulator. The shape of the electrodes as well as the channel diameter can be adapted to any desired purpose.

5 The first electrode 5, the insulator 4 and the second electrode 3 are press fitted together. Furthermore, the electrodes 5, 3 and the insulator 4 are here press fitted to the holder element 7. In Fig. 4, the electrodes 5, 3 and the insulator 4 are shown when mounted in the holder
10 element 7.

The holder element 7 is here conveniently designed according to the purpose, with a cylindrical part for connection to the cathode holder 9, and outwardly extending arms between which the electrodes 5, 3 and the
15 insulator 4 can be press fitted. The connection to the cathode holder 9 is such that the cathode 8 is arranged concentrically with and spaced from the electrode 5 closest to the cathode 8.

The electrode 3 furthest away from the cathode 8 is
20 in contact with an annular gasket 2, which in turn bears against the anode 1.

When assembled, the holder element 7, with the cathode holder 9, is mounted in the plasma-generating portion of the tubular housing 12. The conductor 11 connected at
25 the cathode, and the insulation 10 associated therewith, extends through the gas supply channel 17 in the supply portion of the housing. The anode 1 is connected to the housing 12 and the plasma-generating system has such dimensions relative to the housing 12 that a predetermined
30 compressive force is exerted on the gasket 2 between the anode 1 and the electrode 3 closest thereto. This ensures that a watertight seal is obtained between the anode and the housing 12. The controlling compressive force can be achieved by means of threading between the anode 1 and
35 the housing 12, welding or soldering. In any case, the interconnection of the anode 1 and the housing 12 is such as to provide an electrical contact between the two.

To provide a connection to the gas supply channel 17 the cylindrical portion of the holder element 7 that encloses the cathode 8 is designed to fit in the gas supply channel 17. Moreover, the size of the electrodes and the shape of the arms of the holder element are such as not to prevent the coolant from flowing out and in through the cooling channels 15, 16 and on between the electrodes 5, 3 and the inner wall of the housing 12. The coolant is preferably water, although other fluids are conceivable.

Moreover, to provide a connection to supply units for supplying plasma-generating gas, energy and coolant, a coupling device is provided (detached in Fig. 1). The coupling device comprises two parts, an outlet end 13, which defines coupling channels to be fitted in the channels 15, 16, 17 of the tubular housing 12, and an inlet end 14 provided with hose couplings 18, 19, 20 for coupling hoses to each of said coupling channels. The hose couplings 18, 19, 20 can, for example, be "olive couplings". Furthermore, the coupling device is provided with a conductor opening through which the conductor 11 extends for connection to an energy source.

From the hose couplings 18, 19, 20, flexible hoses conveniently extend to a coupling terminal for connection to a supply unit. Fig. 7 illustrates one example of such a coupling terminal.

Fig. 8 shows the device in Fig. 1 when assembled with a handle portion. In the drawing, one half of the handle portion has been removed, so that the connection to other parts can be seen clearly. The handle portion partially encloses the housing 12 and extends over the coupling device and over a portion of the supply hoses. The housing 12 is here provided with a first contact ring 27, which is connected to earth. This is to ensure that the device has zero potential. In addition, the housing is provided with a second contact ring 24, which is usable to control the earthing of the housing 12.

The handle portion further comprises a printed circuit card 25, which contains, inter alia, an indication component, whose electrical resistance can be read and used to indicate what type of device is being used. In this embodiment, the handle portion is also provided with buttons 26 to switch the device on and off.

Fig. 9 shows the device in Fig. 8 with the whole handle portion. The handle has an ergonomic design that allows it to be held and operated comfortably.

Fig. 10 illustrates a second embodiment of the invention. The tubular housing 12 is here longer than in the embodiment described previously, and the shape of the handle is slightly different. This embodiment is particularly suitable for laparoscopic surgery. The handle
15 portion does not have any buttons and instead the device is switched on and off by means of a footswitch.

Advantageously, the device can be provided as a disposable instrument. The whole device, including housing, coupling device, hoses and coupling terminal, can be sold
20 as a disposable instrument. Alternatively, only the housing and its content may be disposable, and adapted to be connected to non-disposable handles and hoses, etc.

Advantageously, the plasma-generating gas is the same type of gases that are used in prior-art instruments,
25 for example argon.

Other embodiments and variants are conceivable within the scope of the present invention. For example, the number and design of the electrodes may be varied depending on the type of plasma-generating gas used and
30 the desired properties of the plasma. Moreover, the length of the housing, and of its supply portion and plasma-generating portion, respectively, may be varied to fit different applications. The coupling device may be designed in several ways just like the handle. The
35 number of additional channels and their cross section may be varied. For example, three additional channels may be provided, two being used for supplying and discharging a

12

coolant and one being used for sucking liquid from an area of surgery. Furthermore, the housing and the anode may be made in one piece rather than as two units put together according to the embodiment described above.

5

CLAIMS

1. A plasma surgical device for reducing bleeding
5 in living tissue by means of a gas plasma, comprising a
plasma-generating system having an anode (1), a cathode
(8) and a gas supply channel (17) for supplying gas to
the plasma-generating system, the plasma-generating
system comprising at least one electrode (3, 5), which
10 is arranged between said cathode (8) and said anode (1),
and the plasma-generating system being enclosed by a
housing (12) of an electrically conductive material,
which is connected to the anode (1), c h a r a c -
t e r i s e d in that said housing (12) forms said gas
15 supply channel (17).

2. A plasma surgical device according to claim 1,
in which said housing (12), in addition to said gas
supply channel (17), forms at least one additional
channel (15, 16).

20 3. A plasma surgical device according to claim 2,
in which said housing (12), in addition to said gas
supply channel (17), forms at least two additional
channels (15, 16).

4. A plasma surgical device according to claim 3,
25 in which said gas supply channel (17) is arranged at the
centre of the housing (12) and the additional channels
(15, 16) are arranged along the circumference of the gas
supply channel (17).

5. A plasma surgical device according to claim 3 or
30 4, in which said additional channels (15, 16) are cooling
channels for supplying and discharging a coolant.

6. A plasma surgical device according to any one of
the preceding claims, in which the housing (12) forms a
supply portion, in which said gas supply channel (17) is
35 formed, and a plasma-generating portion, in which said
plasma-generating system is provided.

7. A plasma surgical device according to any one of the preceding claims, in which said cathode (8) is connected to a conductor (11) for connection to a voltage source.

5 8. A plasma surgical device according to claim 7, in which said conductor (11) is adapted to extend through one of the channels (15, 16, 17) in said housing (12).

9. A plasma surgical device according to claim 8, in which the conductor (11) extends through a gas supply
10 channel (17) arranged at the centre of said housing (12).

10. A plasma surgical device according to any one of the preceding claims, in which said plasma-generating system comprises at least two electrodes (3, 5), which are insulated from each other by an insulator (4).

15 11. A plasma surgical device according to any one of the preceding claims, in which said at least one electrode (3, 5) is mounted in a holding means (7) made of an electrically insulating material.

20 12. A plasma surgical device according to claim 11, in which said electrodes (3, 5), and an insulator (4) if any, are press fitted to said holding means (7).

13. A plasma surgical device according to claim 11 or 12, in which said cathode (8) is arranged in the holding means (7) concentrically with and spaced from an
25 electrode (5) closest to the cathode (8).

14. A plasma surgical device according to claim 13, in which said cathode (8) is mounted in the holding means (7) by means of a cathode holder (9), which is press fitted to the holding means (7).

30 15. A plasma surgical device according to claim 13 or 14, in which an insulating tube (6) of a ceramic material is mounted on the inside of the holding means (7) so as to enclose the cathode (8).

35 16. A plasma surgical device according to any one of claims 13-15, in which the holding means (7) has a connection end, which is connected to said gas supply channel (17), so that gas is passed through the holding

means (7) to the cathode (8) and then through said at least one electrode (3, 5) towards the anode (1).

17. A plasma surgical device according to claim 16, in which the holding means (7) has an outer shape such as to allow a fluid to flow respectively from and to the additional channels (15, 16) in a space formed between the holding means (7) with said electrode (5, 3), and insulators (4) if any, and the inner wall of the housing (12) at the holding means (7).

18. A plasma surgical device according to any one of the preceding claims, in which a gasket (2) is arranged between the anode (1) and the electrode (3) closest to the anode (1), and the plasma-generating system is arranged in such manner in the housing (12) that the anode (1) is connected to the housing (12), a predetermined compressive force being applied to the gasket (2), so that a watertight seal is established between the housing (12) and the anode (1) and electrical contact therebetween is ensured.

19. A plasma surgical device according to any one of the preceding claims, in which said housing (12) is surrounded by a first contact ring (27) in electrical contact therewith, which contact ring is connected to earth.

20. A plasma surgical device according to claim 19, in which said housing (12) is surrounded by a second contact ring (24), which is capable of being used to constantly control the earthing of the housing (12).

21. A plasma surgical device according to any one of claims 2-19, in which a connecting device is provided for connecting the gas supply to said gas supply channel (17) and any desired function to said additional channels (15, 16).

22. A plasma surgical device according to claim 21, in which said connecting device has an outlet end, which defines connecting channels for obtaining a fluidtight fit in said gas supply channel (17) and additional

channels (15, 16), and an inlet end provided with hose couplings (18, 19, 20) for connecting hoses to each of said connecting channels.

23. A plasma surgical device according to claim 21
5 or 22, in which said connecting device also has a conductor opening through which a cathode conductor (11) extends for connection to a voltage source.

24. A plasma surgical device according to any one
of claims 2-23, in which said housing (12) is connected
10 to hoses for supplying gas and any desired function to the additional channels, which hoses are connected, at their other end, to a connector for connection to a supply unit.

25. A plasma surgical device according to any one
15 of the preceding claims, which comprises a handle portion that at least partially encloses said housing (12) to allow easy handling of the device.

26. A plasma surgical device according to claim 20,
which comprises a circuit adapted to distinguish the
20 device type by means of the resistance of an indication component (25).

27. A plasma surgical device according to any one
of the preceding claims, which has a first button (26)
for switching the plasma generator on and off.

25 28. A plasma surgical device according to claim 27, which, for increased reliability, has a second button (26).

1/6




Fig. 2






Fig. 1

2/6

*Fig. 3**Fig. 4*

3/6




Fig. 5




Fig. 6

4/6




Fig. 7

5/6




Fig. 8

6/6




Fig. 9




Fig. 10

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/01537

A. CLASSIFICATION OF SUBJECT MATTER

IPC: A61B 18/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B

Searched other than minimum documentation to the extent that such documents are included in the fields searched

FI, NO classes as above

Data base consulted during the international search (name of data base and, where practicable, search terms used)

DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3434476 A (R.F. SHAW ET AL), 25 March 1969 (25.03.69), abstract, fig. --	1-27
A	WO 9606572 A1 (NIKVAL INTERNATIONAL AB), 7 March 1996 (07.03.96), abstract, fig. --	1-27
A	US 3858072 A (VLADIMIR DEMBOVSKY), 31 December 1974 (31.12.74), abstract, fig. --	1-27
A	US 6475215 B1 (NAIM ERTURK TANRISEVER), 5 November 2002 (05.11.02), abstract, fig. --	1-27

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

4 December 2003

Date of mailing of the international search report

11-12-2003

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Hélène Erikson/El
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/01537

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3938525 A (ROBERT G. COUCHER), 17 February 1976 (17.02.76), abstract, fig. --	1-27
A	US 5320621 A (MARK G. GORDON ET AL), 14 June 1994 (14.06.94), abstract, fig. -- -----	1-27

INTERNATIONAL SEARCH REPORT
Information on patent family members

06/09/03

International application No.

PCT/SE 03/01537

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	3434476	A	25/03/69	NONE	
WO	9606572	A1	07/03/96	AU 7865794 A SE 503334 C SE 9301850 A EP 0784452 A,B JP 10504751 T US 5843079 A	22/03/96 28/05/96 02/12/94 23/07/97 12/05/98 01/12/98
US	3858072	A	31/12/74	BE 795236 A CH 550528 A CS 163895 B DD 101585 A DE 2306022 A,B,C FR 2171418 A,B GB 1416783 A JP 48089149 A SE 378998 B,C	29/05/73 14/06/74 07/11/75 12/11/73 23/08/73 21/09/73 10/12/75 21/11/73 22/09/75
US	6475215	B1	05/11/02	AU 2397202 A CA 2425257 A EP 1330200 A US 2003069576 A WO 0230308 A	22/04/02 18/04/02 30/07/03 10/04/03 18/04/02
US	3938525	A	17/02/76	NONE	
US	5320621	A	14/06/94	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.